



ESBOvalve

# A 202

The A 202 is a silicone-free, blow-off proof ball valve with two-piece body and threaded ends



## ESB0valve

# A 202

The ESB0valve A 202 is a ball valve with two-piece body and threaded ends. It is silicone-free and has a blow-off proof stem design.



### Technical data

Through-bore	1/4" – 2"
Overall length	DIN 3202 M3
Pressure class	PN 100 (1/4" – 1"), PN 63 (1 1/4" – 2")
Enclosure, end cap, ball	1.4408 (316)
Spindle	1.4401 (316)
Thrust washer, spring washer, nut	1.4401 (316)
O-ring	PTFE
Ball seal, sliding ring, packing box, etc.	PTFE, TFM 1600 or RTFE
Handle	1.4301 (304), plastic covering
Threaded ends	DIN EN 10226-1 (previously DIN 2999-1), NPT or BS
Actuators	Hand lever

## Dimensions

Size	Bore	ØD	L
1/4"	DN 8	11,6	50
3/8"	DN 10	12,7	60
1/2"	DN 15	15	75
3/4"	DN 20	20	80
1"	DN 25	25	90
1¼"	DN 32	31,8	110
1½"	DN 40	38	120
2"	DN 50	50,8	140

ØD: Bore diameter of the ball

L: Face-to-face length of the ball valve  
All dimensions in millimeters (mm)

## Approvals

TR-Certificate of the Russian Federation



**ESBO-Edelstahl  
Rohre und Verbindungsteile GmbH**

Erbsengasse 28  
D-69469 Weinheim  
Germany

Phone +49 6201 63081  
Fax +49 6201 17917

[info@esbo-edelstahl.com](mailto:info@esbo-edelstahl.com)  
[www.esbo-edelstahl.com](http://www.esbo-edelstahl.com)